

Package: parqr (via r-universe)

October 6, 2026

Type Package

Title Read in Multi-Part Parquet Files

Version 0.1.0

Description Reads in multi-part parquet files. Will read in parquet files that have not been previously coalesced into one file. Convenient for reading in moderately sized, but split files.

URL <https://github.com/jhnwllr/parqr>

License CC0

BugReports <https://github.com/jhnwllr/parqr/issues>

Encoding UTF-8

RoxygenNote 7.1.1

Language en-US

Imports purrr, arrow, magrittr

Suggests testthat (>= 3.0.0), knitr, rmarkdown

Config/testthat/edition 3

VignetteBuilder knitr

Config/pak/sysreqs cmake libssl-dev

Repository <https://jhnwllr.r-universe.dev>

Date/Publication 2022-01-26 14:46:14 UTC

RemoteUrl <https://github.com/jhnwllr/parqr>

RemoteRef HEAD

RemoteSha 2b77af35fa08cf0bdbfad38cabe7448b1c59b36a

Contents

parquet_readr	2
parquet_readr_list	2

Index	4
--------------	----------

parquet_readr	<i>Read a multi-part parquet file in as a data.frame</i>
---------------	--

Description

Read a multi-part parquet file in as a data.frame

Usage

parquet_readr(path, verbose = FALSE)

Arguments

- path The path to the directory where the file is stored.
- verbose Used for debugging the path string.

Value

A single dataframe of your multi-part parquet.

Examples

```
## Not run:
# parquet_readr(path=path/to/your/parquet.parquet)

## End(Not run)
```

parquet_readr_list	<i>parquet_readr_list</i>
--------------------	---------------------------

Description

parquet_readr_list

Usage

parquet_readr_list(path, verbose = FALSE)

Arguments

- path The path to the directory where the file is stored.
- verbose For debugging the path string.

Value

A list of dataframes.

Examples

```
## Not run:  
# parquet_readr_list(path=path/to/your/parquet.parquet)  
  
## End(Not run)
```

Index

parquet_readr, [2](#)
parquet_readr_list, [2](#)